



Overview

The membrane base plates by Secabo create new opportunities in the implementation of your Secabo heat press - especially when working with transfer objects with significant height-differences and unevenness. Many old and almost all new heat press models allow for upgrading to the passive membrane lower plates. The membrane can easily be inflated via a small inflation bulb. The membrane's maximum compensation height may be configured thereby. As usual, the contact pressure is set on the heat press, for example via a hand wheel on the heat plate. When the heat press is closed, a manometer reliably displays the current contact pressure - in grams per square centimeter. The pressure can be adjusted via the inflation bulb and a release valve. The membrane lower plates by Secabo allow for taking accurate readings of the actual contact pressure, as well as reproducibly setting it. The membrane lower plates are available for work surfaces of 38cm x 38cm and 40cm x 50cm. The plates' actual dimensions are 45 x 45cm and 47 x 57cm respectively. It is possible to mount them straight to the base of many Secabo heat presses and they are compatible with the well-known quick change systems and slide extensions by Secabo.

Membrane base plate 47cm x 57cm for TC7, TC7 SMART / LITE, TPD7 / TPD7 PREMIUM, TS7 swingaway / TS7 **Technical Data** SMART

dimensions	47cm x 57cm x 5,5cm
pressure setting	Adjustment on the transfer press, fine adjustment via blower ball and drain valve
working area	40cm x 50cm
scope of delivery	Diaphragm base plate with screw-on base, fixing material
max. working pressure	Up to 500 depending on the performance data of the heat press g/cm ²
max temperature	230 °C
environment	5°C - +35°C/ 30% - 70% humidity
weight without packaging	10 kg
weight with package	15,00 kg
Brand	Secabo

Membrane base plate 47cm x 57cm for TC7, TC7 SMART / LITE, TPD7 / TPD7 PREMIUM, TS7 swingaway / TS7 SMART

Views



